

CINTA ALUMINIO CLIMAVER 335

DESCRIPTION

46µ soft aluminium foil with acrylic adhesive system and a siliconized paper liner.

APPLICATIONS

- Closing rigid air duct insulation.
- Heat reflector.
- Applications requiring detection by photoelectric equipment.

PRODUCT BENEFITS

- Very soft and very conformable.
- Easy to tear.
- Same aluminium appearance as air duct.
- Temperature resistance : -20°C to +110°C.



TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Total Thickness	mm	0.08	AFERA 4006
Tensile Strength	N/cm	25	AFERA 4004
Elongation at Break	%	5	AFERA 4005
Adhesion to Steel	N/cm	5	AFERA 4001
Adhesion to Backing	N/cm	5.5	AFERA 4001
U.L. classification : • Flame spread • Smoke developed	-	5 0	U.L. 723

STANDARD PRESENTATION

- Roll length: 50m
- Roll width: 50, 75, 100mm
- Core: 76mm cardboard
- Branding: Scapa
- Packaging: Rolls: Bulk pack with interleaving.

RECOMMENDATIONS

Rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. The storage temperature should be between +10°C and +25°C. Under these conditions, the storage life of the tape in a temperate climate will be at least 12 months.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.

